

Model Number

2100E21-400

# SMARTAMP POWER AMPLIFIER FOR POWERING ELECTRODYNAMIC EXCITERS

Revision: NR

ECN#:

## PERFORMANCE

Amplifier Efficiency	92% <sup>[1]</sup>
Output Voltage (max)	38 V RMS <sup>[2]</sup>
Current Limit	18 A peak <sup>[3]</sup>
Output Power	400 W <sup>[4]</sup>
Distortion	< 0.1% <sup>[5]</sup>
Frequency Response (+0 to -3 dB, 4 Ω load)	0.4 to 40,000 Hz
Voltage Gain (max)	26 dB
Input Impedance	10 kΩ
Output Impedance	30 mΩ <sup>[6]</sup>
Cooling	Convection <sup>[7]</sup>
Protection Features	Interlock Switch, DC Fault Detection, Clip Detection, Over-Current Detection/Over-Temperature Detection, Safe Start in Mute Mode

### NOTES:

- [1] At full power output
- [2] At 4 Ω load impedance, 1 kHz, THD 0.1%
- [3] Typical, over-current protection limited
- [4] At 4 Ω load impedance, 1 kHz, THD 0.04%
- [5] Typical, THD + noise 10 Hz – 20 kHz, 2 Ω load, 50 W
- [6] At frequencies less than 1 kHz
- [7] 40 mm silent fan, automatically controlled

## ELECTRICAL

Input Power, Voltage	100-120 or 220-240 VAC
Input Power, Frequency	48 to 62 Hz

## PHYSICAL

Size (Height x Width x Depth)	3.5 in x 17.3 in x 14.6 in (9 cm x 44 cm x 37 cm)
Weight	8.5 lb (3.8 kg)
Input Connector	BNC Jack
Output Connectors	Screw Terminals
Interlock Connectors	Screw Terminals
Front Panel UI	Two row character LCD, four function keys

## SUPPLIED ACCESSORIES

- Power Cable
- Rack Mounting Brackets
- Rubber Feet
- Spare Fuses

All specifications are at room temperature unless otherwise specified.  
 ICP® is a registered trademark of PCB Piezotronics, Inc.  
 In the interest of constant product improvement, specifications may change without notice.



Project Engineer:

*MAP*

Product Manager:

NEW

SAM Team Leader:

*CAO*

Spec Number:

PS-0153

Date: 9/29/20

Date: 9/29/20

Date: *9/28/20*

Page 1 of 1



10310 Aerohub Boulevard  
 Cincinnati, OH 45215, USA

info@modalshop.com  
 +1 513.351.9919

+1 800.860.4867  
 Fax: +1 513.458.2172

SAM-F020 revB 05/17/18